

PRODUCT PARAMETERS				
Feature				
1.1	Model			CPD15 Cast Iron
1.2	Power Type			Electric
1.3	Operation Type			Sitting - type
1.4	Load Capacity	Q	kg	1500
1.5	Load Center Distance	C	mm	500
1.6	Front Overhang	X	mm	340
1.7	Wheelbase	y	mm	1470
Weight				
2.1	Self - weight (including battery)		kg	2350
Tire and Chassis				
3.1	Tire Type, Drive Wheel/Steering Wheel			Solid Tire
3.2	Drive Wheel Size (Diameter x Width)		mm	18X7-10
3.3	Steering Wheel Size (Diameter x Width)		mm	400 - 8
3.4	Quantity of Drive Wheels, Steering Wheels (x = Drive Wheels)			2X/2
3.5	Drive Wheel Track (distance of two Front wheels)	b10	mm	950
3.6	Steering Wheel Track (distance of two rear wheels)	b11	mm	920
Dimensions				
4.1	Mast and Fork Tilt Angle Forward/Backward	α/β	6°/10°	
4.2	Height after Lowering of the Mast	h1	mm	2150
4.3	Maximum Lifting Height	h3	mm	3000
4.4	Mast Height Maximum Extended	h4	mm	3960
4.5	Height of Protective Roof (Driver's Cabin)	h6	mm	2120 (Without lights)
4.6	Height of Seat	h7	mm	1080
4.7	Height of Trailer Pin Center	h10	mm	500
4.8	Overall Length of the Vehicle	l1	mm	3305
4.9	Length to the Vertical Plane of the Fork	l2	mm	2200
4.10	Overall Width	b1/b2	mm	1100
4.11	Fork Size	s/e/l	mm	35X100X1070
4.12	Dimensions of Fork Carriage Outer	b3	mm	1040
4.13	Clearance from the Ground when the Full - load Mast is Lowered	m1	mm	110
4.14	Minimum Ground Clearance of the Vehicle Body	m2	mm	100
4.15	Aisle Width (Pallet 1200mm *1000mm Clear 200mm)	Ast	mm	3360
4.16	Aisle Width (Pallet 800mm *1200mm Clear 200mm)	Ast	mm	3560
4.17	Turning Radius	Wa	mm	1985
Performance				
5.1	Travel Speed, Loaded/Unloaded		km/h	10./12.
5.2	Lifting Speed, Loaded/Unloaded		m/s	0.24/0.3
5.3	Lowering Speed, Loaded/Unloaded		m/s	0.35/0.32
5.4	Maximum Climbing Ability, Loaded/Unloaded (Gradeability)		%	15
5.5	Service Brake Type			Hydraulic+Mechanical
5.6	Parking Brake Type			Mechanical
Motor and Battery				
6.1	Rated Power of Drive Motor S2 for 60 minutes		kW	5
6.2	Rated Power of Lifting Motor S3 15%		kW	5
6.3	Rated Capacity of Battery		Ah	
6.4	Drive Control Type			AC

*Subject to change without notice for technical parameter modifications. The schematic diagram may not be the actual configuration.